

B) Stock: Class designation: S. These mowers are as delivered from the factory except for the modifications listed below.

- 1) Engine must be originally manufactured for use in lawn mowing equipment and be stock, with the exception of air filter, air cleaner or velocity stack. Crankshaft must be in original orientation and clearance hole in the frame. Engine must be stock . Max size is 28 cid. Flathead and OHV up to 15 horsepower..
- 2) Exhaust design is open, but must terminate away from driver and competitors, in a rearward and/or downward direction and present no apparent safety hazard.
- 3) Starter must be onboard electric.
- 4) Driveline may be modified from the engine pulley to the rear wheels, but must utilize a shiftable lawnmower transaxle. No jackshafts. Single belt driven.
- 5) Rear axle may use open or locked axle. No single wheel drive.
- 6) No centrifugal and or torque converter clutches.
- 7) Rear axle should use shaft locks, center bolts, or thru-bolts to secure the rear wheels.
- 8) All steering linkages must use ball-type or spherical threaded rod ends.
- 9) Front axle may be pinned, bolted or welded into stock position. No suspension, no shock absorbers. Axles must have a 1-piece beam.
- 10) Front axle and steering must be stock for that manufacturer. Must be Stock L spindles
- 11) Shaft locks, center-drilled axle with locking bolts, castellated nuts with cotter pins, are acceptable for securing front wheels. Cotter pins, E-rings and C-rings alone, bent nails, hitch pins, over-center pins and quick-release pins are not sufficient for wheel retention and are not approved.
- 12) Wheels must be the same size on each axle, of any origin, made of steel. No dual or tandem wheels. 6 inch min. 8 inch max. Should be reinforced.
- 13) Lawnmower tires must be used.
- 14) Footholds must be discrete, and no more than 2" high, made of flat or "L" stock (no rod stock), and made such that the foot can not become entangled in a rollover.
- 15) Minimum frame height is 6 inches.
- 16) All parts should be of lawn mower origin with the exception of those specifically mentioned above or otherwise allowed under Sec. VII.
- 17) Hoods and body parts such as fenders may be upgraded from year to year only if the parts are from the mother company and any subsidiary company of said mother company.
- 18) External ignition Systems are not allowed.
- 19) Aluminum Flywheels are not allowed.
- 20) Fenders may be discreetly moved but not altered.

4/22/10

21. See other rules for bumper and mower decks.